SpeechMike Premium Touch Dictation microphone

SMP3700/3800 Find similar products >

Connectivity

USB:	highspeed USB 2.0

Audio recording

Microphone type:	electret condenser microphone
Microphone capsule:	10 mm
Characteristic:	uni-directional
Frequency response:	200 – 12 000 Hz
Sensitivity:	-37 dBV
Signal-to-noise ratio:	> 70 dBA

Sound

Speaker type:	built-in round, dynamic speaker
Speaker diameter:	30 mm
Acoustic frequency response:	300 – 7500 Hz
Speaker output power:	> 200 mW

Barcode scanner (SMP3800/3810)

Compatible bar codes:		EAN, UPC, Code 11 / 39 / 93 / 128, Codabar, MSI Code,	
		Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Matrix	
Overview	Versions	2 of 5 Specifications	Support
Type: Charge-coupled device (CCD)			

System requirements for Philips SpeechExec software

Processor:	Intel dual core or equivalent AMD processor, 1 GHz or faster processor
RAM:	2 GB (32 bit)/4 GB (64 bit)
Hard-disk space:	100 MB for SpeechExec software, 4.5 GB for Microsoft .NET Framework
Operating system:	Windows 10 (64 bit), Windows 8.1/7 (32/64 bit), Windows Server 2012 (64 bit), Windows Server 2008 R2 (32/64 bit)
Graphics:	DirectX-compliant graphics card with hardware acceleration recommended
Sound:	Windows-compatible sound device
Browser:	Internet Explorer 9 or higher, or the current version of Chrome or Firefox
Free USB port	
Internet connection for required software activation	

Additional system requirements for speech recognition software

Supported speech recognition software:	Nuance Dragon Professional 12.5/13/14/15 Individual/Group, Nuance Dragon Legal 12.5/13/14/15, Dragon Medical Practice Edition 2/3, Nuance Dragon SDK Client Edition 14, M*Modal Fluency Direct 8.0 and above
Processor:	Intel dual core or equivalent AMD processor, 2.2 GHz or faster processor
RAM:	4 GB (32 bit)/8 GB (64 bit)
Hard-disk space:	8 GB
Operating system:	Windows 10 (64 bit), Windows 8.1/7 (32/64 bit), Windows Server 2012 (64 bit), Windows Server 2008 R2 (32/64 bit)

Green specifications

Compliant to 2011/65/EU (RoHS)

Lead-free soldered product

Operation conditions

Temperature:	5° – 45° C / 41° – 113° F
Humidity:	10 % – 90 %

Dimensions

Product dimensions (W × D × H):	45 × 175 × 32 mm / 1.8 × 6.9 × 1.25 in
Weight:	200 g / 7 oz (including cable)
Cable length:	2.5 m / 8.2 ft

Design and finishing

Material:	housing made of high-class polymers with antimicrobial additive
Color:	dark grey pearl metallic,

Package contents	
SpeechMike Premium Touch dictation microphone	
USB cable (connected to device)	
Microphone holder	
Quick start guide	

© Speech Processing Solutions. All rights reserved.